

VP-31MX-M/C 35 H

31MP Thermoelectric Peltier Cooled Camera



CoaXPress®

The VP-31MX-35 H, the latest model of the industrial proven VP series, is a new 31 megapixel CoaXPress camera and based on the latest CMOS image sensor technology (IMX342) from Sony Semiconductor Solutions Corporation. The VP-31MX-35 H offers up to 35.4 frames per seconds at 6464 × 4852 resolution. This camera uses thermo-electric Peltier (TEC) cooling technology developed for and used by many demanding medical market customers. The TEC maintains the operating temperature of the image sensor at up to $15 \pm 2^{\circ}\text{C}$ below ambient temperature. The VP-31MX camera provides a stable operating condition and the ability to expose for a long period of time to increase the camera's sensitivity. Featuring high-speed and high-resolution with stable performance, this camera is ideal for demanding applications such as FPD, PCB and semiconductor inspections.

VIEWWORKS

www.viewworks.com

VP-31MX-M/C 35 H

31MP Thermoelectric Peltier Cooled Camera

Main Features

- Thermoelectric Peltier Cooled – $15 \pm 2^{\circ}\text{C}$ below
- 31 Megapixel Resolution
- CoaXPress Interface up to 35.4 fps at 25 Gbps using 4 CH
- Flat Field Correction with Sequencer Control
- PRNU Correction
- Hot Pixel Correction
- Defective Pixel Correction
- Frame Averaging
- GenICam Compatible – XML based Control

Applications

- Flat Panel Display Inspection
- Electronics Inspection
- Semiconductor Inspection
- Document / Film Scanning


Specifications

Model		VP-31MX-M/C 35 H
Resolution (H × V)		6464 × 4852
Sensor		SONY IMX342
Optical Format (Diagonal)		APS-C (27.9 mm)
Pixel Size		3.45 μm × 3.45 μm
Interface		CoaXPress (CXP-3 / CXP-6)
Max. Frame Rate	8 bit	35.4 fps
	10 bit	35.4 fps
	12 bit	25.8 fps
Exposure Time		2.4 μs – 60 s
Partial Scan (Max. Speed)		1464.7 fps at 4 Lines
Binning	Sensor	×1, ×2 (Horizontal and Vertical Dependent)
Pixel Data Format	Mono	Mono 8 / Mono 10 / Mono 12
	Color	RG Bayer 8 / RG Bayer 10 / RG Bayer 12
Electronic Shutter		Global Shutter
Trigger Synchronization		Free-Run, Hardware Trigger, Software Trigger or CXP
External Trigger		3.3 V ~ 24.0 V, 10 mA, Logical Level Input, Optically Isolated
Software Trigger		Asynchronous, Programmable via Camera API
Dynamic Range		72 dB
Gain Control		1× ~ 32×
Black Level Control		0 ~ 255 LSB at 12 bit
Cooling Method		Thermoelectric Peltier Cooling
Cooling Performance		$15 \pm 2^{\circ}\text{C}$ below ambient temperature – Standard cooling with a fan
Dimension / Weight		90.0 mm × 90.0 mm × 129.3 mm, 1261.4 g (with F-mount)
Temperature		Operating: 0°C ~ 40°C , Storage: -40°C ~ 70°C
Lens Mount		F-mount, Custom mount available upon request
Power	External	11 ~ 24 V DC
	Dissipation	Typ. 30.0 W
Compliance		CE, FCC, KC (in preparation)
API SDK		Viewworks Imaging Solution 7.X


VP-31MX-M/C 35 H

31MP Thermoelectric Peltier Cooled Camera

Relative Sensitivity Curves



Ordering Scheme




Connector Specification

Power




1, 2, 3: +12V DC
4, 5, 6: GND
(HR10A-7R-6PB)

Control



1: Trigger IN+
2: Trigger IN-
3: Strobe OUT-(GND)
4: Strobe OUT+
(HR10A-7R-4S)

Data Transfer / Communications



CH1 CH2 CH3 CH4

CH1: Master Connection
75 Ω, DIN 1.0/2.3



Connectors on camera body

VP-31MX-M/C 35 H

31MP Thermoelectric Peltier Cooled Camera

Mechanical Dimensions

Unit: mm



최적의 ALL-IN-1 솔루션을 제안합니다.

솔루션, 제품, 서비스에 대해 궁금하신 내용을 남겨주시면 빠른 시일 내로 회신 드리겠습니다.



공식 홈페이지



공식 블로그



공식 인스타그램

제품·기술지원 문의

☎ 02-6914-6363

✉ b2s@b2s.kr