

<NVA1500CL-M-KN>

CIS-type Line Camera



- WD=17mm
- Resolutions=600dpi
- Monochrome Output
- Scan length=1,523mm
- CameraLink I/F

Specification

	unit	NVB1500CL-M-KN	(Reference) NVB300CL-M-KN
Scan Length	mm	1,523	304
WD	mm	17	
Total Pixels / Line (It contains duplicate pixels)	pixel	36,720	7,344
Color Type	—	Monochrome	
Resolutions	dpi	600 / 300 (switchable)	
Pixel Pitch	μm	42.3	
Line Rate (Max.)	kHz	37.9 (600dpi), 70.6 (300dpi)	
Scan Speed (Max.)	m/min	96 (600dpi, C/L Full config.)	
Interface (Connectors)	—	CameraLink	
	Base	5	1
	Medium/Full	10	2
Lighting	—	None	
Power Supply	V	DC 24	

Functions

Functions	Y/N	Functions	Y/N
Flat Field Correction (FFC)	Y	Save Parameters	Y
Dark Frame Subtraction	Y	Overheating Protection	Y
Gain Control	Y	Staggered Pixel Shift	Y

Note) Values in these tables are not warranted. Specification and appearance are subject to change without notice.

Depth of Field

Ex. NVB300CL


[Object] printed letters (8pt size)

Distance from Lens (mm)						
47	48	49	50	51	52	53
強	強	強	強	強	強	強

Note) Captured images are samples, are not warranted.

Sensor Layout


Staggered layout:



Set-Up


Ex. NVB300CL

CameraLink connector DC24V Power supply



(Image Processing Software is not included)

Dimension



Note) Specification and appearance are subject to change without notice.

최적의 ALL-IN-1 솔루션을 제안합니다.

솔루션, 제품, 서비스에 대해 궁금하신 내용을 남겨주시면 빠른 시일 내로 회신 드리겠습니다.



공식 홈페이지



공식 블로그



공식 인스타그램

제품·기술지원 문의

☎ 02-6914-6363

✉ b2s@b2s.kr