

Object plane

φ62.8

35

(390.66)

Logo

M52×P0.75

EXP

16° 8° 5.6 4.0

79.97

V-mount

φ56⁰_{-0.03}

166.36

192.71

636.99


Image

Main Specification				Image space NA		0.07	
Magnification	0.43X	0.5X	0.57X	Object space NA		0.04	
Working Distance	437.5±5	390.66±5	354±5	Entrance pupil diameter		ø33	
Conjugate Distance	674±9	636.99±9	611±9	Entrance pupil position		58	
Flange Focal Distance	181±0.5	192.71±0.5	202±0.5	Exit pupil diameter		ø31	
Max image circle	ø82			Exit pupil position		-212	
F/#	4.0-16						
EFL	120						
Distortion	0.002%						
IMAGE QUALITY							
AXIS	ø46.2	ø66	ø82				
200lp/mm	160lp/mm	125lp/mm	125lp/mm	标记	处数	更改文件号	担当 变更日期

注:

Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE:
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE±30'
DRAFT ANGLES AREA±0.5°/SIDE



材料(环保)

单位

比例

mm

1:1

设计 朱周德 2015-05-05

名称

LS1605B技术规格图

页码

1/1

校对

审核

代号

LS1605B-SPEC

版本

V0

标记 处数 更改文件号 担当 变更日期

批准