

Object plane

Ø61.8

35

(143.02)

Ø54.5

Logo

M52×P0.75

79.97

EXP

EP

V-mount

16.8 5.6 4.0

757.63

Ø56-0.03

Image

534.64

568.28

Main Specification

Magnification	2.4X	3X	3.8X
Working Distance	155.3±5	143.02±5	128.8±5
Conjugate Distance	681±9	757.63±9	864.5±9
Flange Focal Distance	479.1±0.5	568.28±0.5	585±0.5
Max image circle	Ø82		
F/#	4.0-16		
EFL	120		
Distortion	0.001%		

Image space NA 0.03

Object space NA 0.09

Entrance pupil diameter 31.4

Entrance pupil position 45.2


Exit pupil diameter 32.6

Exit pupil position -593

注:

Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE:
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE ±30°
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保)

单位

比例

mm

1:1

设计 朱周德 2015-06-01

校对

审核

批准

名称

代号

LS1630B技术规格图

LS1630B-SPEC

页码

1/1

版本

V0

IMAGE QUALITY

AXIS	Ø46.2	Ø66	Ø82
100lp/mm	100lp/mm	80lp/mm	80lp/mm

标记 处数

更改文件号

担当

变更日期